## PART NUMBER 1402P-WHT-500

UL Listed and Rated Type CL3P Multi-Conductor Non-Shielded Plenum Cable

■ 0275/0725 FT •

SMARTWIRE(TM)

DEVICE/ZONE A B C D E 0 1 2 3 4 5 6 7 8 9





## **CABLE SPECIFICATIONS**

**DESCRIPTION** 14 AWG 2 twisted Conductor Bare Copper, Non-Shielded Plenum, UL Listed (UL) CL3P

**CONDUCTOR** 14 (19/27 Bare Copper) **INSULATION** Low-Smoke PVC .008"

**COLOR CODE** Black/White

**LAY LENGTH** 3.75" LHL (approx. 3.2 TPF)

SHIELD N/A

**DRAIN WIRE** N/A

JACKET Low-Smoke PVC .018"

JACKET COLOR White Jacket

MARKING SMARTWIRE DEVICE / ZONE A B C D E 0 1 2 3 4 5 6 7 8 9 14 AWG (UL) CL3P ROHS MADE IN

THE USA

OVERALL DIAMETER .210" Nom.

CABLE WEIGHT 40 Lbs/Mft.

**CAPACITANCE** 36 pF/Ft. Nom.

IMPEDANCE 52 Ohms

DC RESISTANCE 2.62 Ohms/mft @ 20 deg C

**TEMPERATURE RATING** 0 C to 75 C / 300 Volt

## **INDUSTRY STANDARDS**

**FLAME RATING** Approved For Plenum Use Without Conduit Per NFPA 262 Flame Test

AGENCY APPROVALS NEC Article 800; UL Listed (UL) CL3P, RoHs Compliant, Made in the USA



