

PART NUMBER 1402P-WHT

UL Listed and Rated Type CL3P Multi-Conductor Non-Shielded Plenum Cable



CABLE SPECIFICATIONS

DESCRIPTION	14 AWG 2 twisted Conductor Bare Copper, Non-Shielded Plenum, UL Listed (UL) CL3P
CONDUCTOR	14 (19/27 Bare Copper)
INSULATION	Low-Smoke PVC .008"
COLOR CODE	Black/White
LAY LENGTH	3.75" LHL (approx. 3.2 TPF)
SHIELD	N/A
DRAIN WIRE	N/A
JACKET	Low-Smoke PVC .018"
JACKET COLOR	White Jacket
MARKING	SMARTWIRE DEVICE / ZONE A B C D E 0 1 2 3 4 5 6 7 8 9 14 AWG (UL) CL3P ROHS MADE IN THE USA
OVERALL DIAMETER	.210" Nom.
CABLE WEIGHT	40 Lbs/Mft.
CAPACITANCE	36 pF/Ft. Nom.
IMPEDANCE	52 Ohms
DC RESISTANCE	2.62 Ohms/mft @ 20 deg C
TEMPERATURE RATING	0 C to 75 C / 300 Volt

INDUSTRY STANDARDS

FLAME RATING	Approved For Plenum Use Without Conduit Per NFPA 262 Flame Test
AGENCY APPROVALS	NEC Article 800; UL Listed (UL) CL3P, RoHS Compliant, Made in the USA



All specifications referenced are nominal measurements unless otherwise noted.



WINDY CITY WIRE • T 800.379.1191 • windycitywire.com

© Windy City Wire, Cable Technology & Products, LLC.
All rights reserved.