


PART NUMBER 1402PFA-MCF-RED-500

UL Listed and Rated Type FPLP / FAMC



CABLE SPECIFICATIONS

DESCRIPTION	14 AWG 4 Conductor Bare Copper, Non-Shielded Plenum Fire Alarm, FPLP (UL)
CONDUCTOR	14 (Solid Bare Copper)
INSULATION	Low-Smoke PVC .010"
COLOR CODE	Black/Red/Brown/Blue
JACKET	Low-Smoke PVC .018"
JACKET COLOR	Red Jacket
MARKING	FIRE/LIFE SAFETY CONTROL CABLE INIT. / IND. DEVICE / ZONE A B C D E 0 1 2 3 4 5 6 7 8 9 14 AWG FPLP (UL) ROHS MADE IN THE USA
OVERALL DIAMETER	Overall MC Diameter = .525" Nom. MC Armor Material = Aluminum
CABLE WEIGHT	111 Lbs/Mft.
CAPACITANCE	26 pF/Ft. Nom.
IMPEDANCE	72 Ohms
TEMPERATURE RATING	0 C to 75 C / 300 Volt

INDUSTRY STANDARDS

FLAME RATING	APPROVED FOR PLENUM USE WITHOUT CONDUIT PER NFPA 262 FLAME TEST
AGENCY APPROVALS	UL 62, 83, 910, 1424, 1479, 1569, 1581 NEC 300.22(C), 330, 430-472, 518, 530, 645, 727, 760.71(D) COMPLIES WITH FEDERAL SPECIFICATIONS A-A-59544(FORMERLY J-C-30B) NEC ARTICLE 760;FPLP (UL), ROHS COMPLIANT, MADE IN THE USA



All specifications referenced are nominal measurements unless otherwise noted.



WINDY CITY WIRE • T 800.379.1191 • windycitywire.com

© Windy City Wire, Cable Technology & Products, LLC.
All rights reserved.