

PART NUMBER 1402PFA-NYC-RED-YLW

UL Listed and Rated Type FPLP Multi-Conductor Non-Shielded Fire Alarm

■ 0275/0725 FT ● FPLP 14 AWG 150C. (UL) ALSO CLASSIFIED NYC CERTIFIED FIRE ALARM CABLE ABCDE0123456789



CABLE SPECIFICATIONS

DESCRIPTION	14 AWG 2 Conductor Bare Copper, Non-Shielded Plenum NYC Fire Alarm, FPLP (UL)
CONDUCTOR	14 (Solid Bare Copper)
INSULATION	FEP .015"
COLOR CODE	Black/Red
SHIELD	N/A
DRAIN WIRE	N/A
JACKET	Sole-F PVDF .025"
JACKET COLOR	Red Jacket with Yellow Stripe
MARKING	E143244 14 AWG C(UL)US FPLP 150 C ALSO CLASSIFIED NYC CERTIFIED FIRE ALARM CABLE SMART STRIP
OVERALL DIAMETER	.238" Nom
CAPACITANCE	22 pF/Ft.
IMPEDANCE	85 Ohms
TEMPERATURE RATING	OPERATIONAL TEMPERATURE RANGE: -60 C to +150 C

INDUSTRY STANDARDS

FLAME RATING	Approved For Plenum Use Without Conduit Per NFPA 262 Flame Test
AGENCY APPROVALS	NEC Article 760; UL Subjects 13, 910, 1424 & 1581, FPLP (UL), Compliant with New York City Local Law 5 requirements



All specifications referenced are nominal measurements unless otherwise noted.



WINDY CITY WIRE · T 800.379.1191 · windycitywire.com

© Windy City Wire, Cable Technology & Products, LLC.
All rights reserved.