

PART NUMBER 16-04P-WHT

UL Listed and Rated Type CMP Multi-Conductor Non-Shielded Plenum Cable



CABLE SPECIFICATIONS

| | |
|--------------------|--|
| DESCRIPTION | 16 AWG 4 Conductor Bare Copper, Non-Shielded Plenum, UL Listed C(UL)US CMP |
| CONDUCTOR | 16 (19/29 Bare Copper) |
| INSULATION | Low-Smoke PVC .008" |
| COLOR CODE | Black/Red/White/Green |
| SHIELD | N/A |
| DRAIN WIRE | N/A |
| JACKET | Low-Smoke PVC .018" |
| JACKET COLOR | White Jacket |
| MARKING | SMARTWIRE DEVICE / ZONE A B C D E 0 1 2 3 4 5 6 7 8 9 16 AWG C(UL)US CMP ROHS MADE IN THE USA |
| OVERALL DIAMETER | .215" Nom. |
| CABLE WEIGHT | 45 Lbs/Mft. |
| CAPACITANCE | 34 pF/Ft. Nom. |
| IMPEDANCE | 55 Ohms |
| TEMPERATURE RATING | 0 C to 75 C / 300 Volt |

INDUSTRY STANDARDS

| | |
|------------------|---|
| FLAME RATING | Approved For Plenum Use Without Conduit Per NFPA 262 Flame Test |
| AGENCY APPROVALS | NEC Article 800; UL Listed C(UL)US CMP, RoHS Compliant, Made in the USA |



All specifications referenced are nominal measurements unless otherwise noted.