PART NUMBER 1602P-YLW

UL Listed and Rated Type CMP Multi-Conductor Non-Shielded Plenum Cable

■ 0275/0725 FT ●	SMARTWIRE(TN) DEVICE/ZONE	A B C D E 0 1 2 3 4 5 6	789	- SMARTWIRE
_ 01/0,0/10/11/1		, 521102,20112			TECHNOLOGY
CABLE SPECIFICA DESCRI		WC 2 Conductor Baro C	opper, Non-Shielded Ple	num III Listed C(III	
			opper, Non-Shielded Fle		
		19/29 Bare Copper)			
		-Smoke PVC .008"			
COLOF	R CODE Blac	k/White	11.		
S	SHIELD N/A		11. A.		
DRAIN	N WIRE N/A				
Ľ	JACKET Low	-Smoke PVC .018"	4 K		
JACKET	COLOR Yel	ow Jacket			
МА		RTWIRE DEVICE / ZON DE IN THE USA	E A B C D E 0 1 2 3 4 5	6789 16 AWG	C(UL)US CMP ROHS
OVERALL DIA	METER .184	l" Nom.			
CABLE W	EIGHT 25	.bs/Mft.			
CAPACI	TANCE 36	F/Ft. Nom.			
IMPE	DANCE 52	Dhms			
DC RESIS	STANCE 4.13	3 Ohms/Mft max @ 20 C			
TEMPERATURE R	ATING 0 C	to 75 C / 300 Volt			
INDUSTRY STAND		roved For Planum Use W	ithout Conduit Per NFPA	262 Elamo Tost	
AGENCY APPR	IUVALS NEC	Article 800; UL Listed C	(UL)US CMP, RoHS Comp	bilant, Made in the U	SA



All specifications referenced are nominal measurements unless otherwise noted.

WINDY CITY WIRE T 800.379.1191 windycitywire.com
^{© Windy City Wire, Coble Technology & Products, LLC.}
All rights reserved.