PART NUMBER 1602SPBR-WHT-YLW

UL Listed and Rated Type CMP Multi-Conductor Shielded Plenum Cable

■ 0275/0725 FT •

SMARTWIRE(TM)

DEVICE/ZONE

ABCDE0123456789





CABLE SPECIFICATIONS

DESCRIPTION 16 AWG 2 Conductor Bare Copper, Shielded Plenum, UL Listed C(UL)US CMP

CONDUCTOR 16 AWG (19 Strand) Bare Copper

INSULATION Low-Smoke PVC .008"

COLOR CODE Black/Red

> SHIELD Aluminum Mylar

DRAIN WIRE 22 AWG (7 Strand) Tinned Copper

> JACKET Low-Smoke PVC .018"

JACKET COLOR White Jacket with Yellow Stripe

> SMARTWIRE DEVICE/ZONE A B C D E 0 1 2 3 4 5 6 7 8 9 16 AWG C(UL)US CMP ROHS MADE IN MARKING

THE USA

OVERALL DIAMETER .184" Nom.

> CABLE WEIGHT 31 Lbs/Mft.

76 pF/ft Nom. CAPACITANCE

IMPEDANCE 25 Ohms

TEMPERATURE RATING 0 C to 75 C / 300 Volt

INDUSTRY STANDARDS

Approved For Plenum Use Without Conduit Per NFPA 262 Flame Test **FLAME RATING**

AGENCY APPROVALS NEC Article 800; UL Listed C(UL)US CMP, RoHs Compliant, Made in the USA







All specifications referenced are nominal measurements unless otherwise noted.