PART NUMBER 1602SPFA-STR-RED-BLK

UL Listed and Rated Type FPLP Multi-Conductor Shielded Stranded Plenum Fire Alarm

■ 0275/0725 FT ● FIRE/LIFE SAFETY CONTROL CABLE INIT/IND DEVICE/ZONE ABCDE0123456789





CABLE SPECIFICATIONS

DESCRIPTION 16 AWG 2 Conductor Bare Copper, Shielded Stranded Plenum Fire Alarm, FPLP (UL)

CONDUCTOR 16 (19 Strand Bare Copper)

INSULATION Low-Smoke PVC .008"

COLOR CODE Black/Red

SHIELD Aluminum Mylar

DRAIN WIRE 22 AWG 7 Strand Tinned Copper

JACKET Low-Smoke PVC .018"

JACKET COLOR Red Jacket with Black Stripe

MARKING FIRE/LIFE SAFETY CONTROL CABLE INIT. / IND. DEVICE / ZONE - MIT A B C D E 0 1 2 3 4 5 6 7

B 9 16 AWG FPLP (UL) ROHS MADE IN THE USA

OVERALL DIAMETER .184" Nom

CABLE WEIGHT 31 Lbs/Mft.

CAPACITANCE 76 Pf/Ft. Nom.

IMPEDANCE 25 Ohms

TEMPERATURE RATING 0 C to 75 C / 300 Volt

INDUSTRY STANDARDS

FLAME RATING Approved For Plenum Use Without Conduit Per NFPA 262 Flame Test

AGENCY APPROVALS NEC Article 760; FPLP (UL), RoHS Compliant, Made in the USA



