## PART NUMBER 1602SPFA-STR-RED

UL Listed and Rated Type FPLP Multi-Conductor Shielded Stranded Plenum Fire Alarm

■ 0275/0725 FT ● FIRE/LIFE SAFETY CONTROL CABLE INIT/IND DEVICE/ZONE ABCDE0123456789





## **CABLE SPECIFICATIONS**

DESCRIPTION 16 AWG 2 Conductor Bare Copper, Twisted, Shielded Stranded Plenum Fire Alarm, FPLP (UL)

**CONDUCTOR** 16 (19 Strand Bare Copper)

INSULATION Low-Smoke PVC .008"

**COLOR CODE** Black/Red

LAY LENGTH 3.5" LHL (3.4 TPF)

> SHIELD Aluminum Mylar

**DRAIN WIRE** 22 AWG 7 Strand Tinned Copper

> JACKET Low-Smoke PVC .018"

**JACKET COLOR** Red Jacket

> FIRE/LIFE SAFETY CONTROL CABLE INIT. / IND. DEVICE / ZONE A B C D E 0 1 2 3 4 5 6 7 8 9 **MARKING**

16 AWG FPLP (UL) ROHS MADE IN THE USA

OVERALL DIAMETER .184" Nom

> CABLE WEIGHT 31 Lbs/Mft.

CAPACITANCE 76 Pf/Ft. Nom.

**IMPEDANCE** 25 Ohms

TEMPERATURE RATING 0 C to 75 C / 300 Volt

## **INDUSTRY STANDARDS**

**FLAME RATING** Approved For Plenum Use Without Conduit Per NFPA 262 Flame Test

**AGENCY APPROVALS** NEC Article 760; FPLP (UL), RoHS Compliant, Made in the USA





All specifications referenced are nominal measurements unless otherwise noted.