PART NUMBER 1604FA-RED-500

UL Listed and Rated Type CMR or FPLR Multi-Conductor Non-Shielded Non-Plenum Fire Alarm

■ 0275/0725 FT ● FIRE/LIFE SAFETY CONTROL CABLE INIT/IND DEVICE/ZONE ABCDE0123456789





CABLE SPECIFICATIONS

DESCRIPTION 16 AWG 4 Conductor Bare Copper, Non-Shielded Non-Plenum Fire Alarm, UL C(UL) CMR or FPLR

CONDUCTOR 16 (Solid Bare Copper)

PVC .010" **INSULATION**

COLOR CODE Black/Red/Brown/Blue

LAY LENGTH 4.0" LHL (approx. 3 TPF)

> **SHIELD** N/A

DRAIN WIRE N/A

> PVC .018" **JACKET**

JACKET COLOR Red Jacket

> **MARKING** FIRE/LIFE SAFETY CONTROL CABLE INIT. / IND. DEVICE / ZONE A B C D E 0 1 2 3 4 5 6 7 8 9

16 AWG UL C(UL) CMR or FPLR (UL) 75C ROHS MADE IN THE USA

OVERALL DIAMETER .208" Nom

> **CABLE WEIGHT** 53 Lbs/Mft.

26 pF/Ft. Nom. **CAPACITANCE**

IMPEDANCE 72 Ohms

TEMPERATURE RATING 0 C to 75 C / 300 Volt

INDUSTRY STANDARDS

AGENCY APPROVALS NEC Article 760; UL C(UL) CMR, RoHS Compliant, Made in the USA







All specifications referenced are nominal measurements unless otherwise noted.