## PART NUMBER 18-03P-WHT

UL Listed and Rated Type CMP Multi-Conductor Non-Shielded Plenum Cable

■ 0275/0725 FT ●	SMARTWIRE(TM)	DEVICE/ZONE	A  B  C  D  E  0  1  2  3	8456789		SMARTWIRE GL/L TECHNOL		
ABLE SPECIFICAT DESCRI			non Non Chielde		inted C(U) NIC (	CMD		
		18 AWG 3 Conductor Bare Copper, Non-Shielded Plenum, UL Listed C(UL)US CMP 18 (7/26 Bare Copper)						
		moke PVC .008"						
		Black/White/Red						
LAY L	<b>ENGTH</b> 3.25"	LHL (approx. 3.7 TPF)						
S	HIELD N/A							
DRAIN	I WIRE N/A							
ſ	ACKET Low-S	moke PVC .018"						
JACKET	COLOR White	Jacket	- 14					
MA		TWIRE DEVICE / ZONE A IN THE USA	B C D E 0 1 2 3	3 4 5 6 7 8 9	18 AWG C(UL	_)US CMP RO	OHS	
OVERALL DIA	<b>METER</b> .168"	Nom.						
CABLE W	EIGHT 23 Lb	s/Mft.				R		
CAPACI	TANCE 27 pF	′Ft. Nom.		_				
IMPE	DANCE 70 Oh	ms						
TEMPERATURE R	ATING 0 C to	o 75 C / 300 Volt						

## INDUSTRY STANDARDS

FLAME RATING	Approved For Plenum Use Without Conduit Per NFPA 262 Flame Test
AGENCY APPROVALS	NEC Article 800; UL Listed C(UL)US CMP, RoHs Compliant, Made in the USA



All specifications referenced are nominal measurements unless otherwise noted.

WINDY CITY WIRE T 800.379.1191 windycitywire.com 
<sup>© Windy City Wire, Coble Technology & Products, LLC.</sup>
All rights reserved.