

PART NUMBER 180209


UL Listed and Rated Type CMP Multi-Conductor Shielded Plenum Cable

■ 0275/0725 FT ●

SMARTWIRE(TM)

DEVICE/ZONE

ABCDE0123456789



CABLE SPECIFICATIONS

DESCRIPTION	18 AWG 1 Triad Tinned Copper, Shielded Plenum, UL Listed C(UL)US CMP
CONDUCTOR	18AWG (19X.0092) Tinned Copper
INSULATION	Low-Smoke PVC .008"
COLOR CODE	Black/White/Red
LAY LENGTH	3.25" LHL (approx. 3.7 TPF)
SHIELD	Aluminum Mylar
DRAIN WIRE	24 AWG 7 Strand Tinned Copper
JACKET	Low-Smoke PVC .017"
JACKET COLOR	Blue Jacket
MARKING	SMARTWIRE DEVICE / ZONE A B C D E 0 1 2 3 4 5 6 7 8 9 18 AWG C(UL)US CMP ROHS MADE IN THE USA
OVERALL DIAMETER	.168" Nom.
CABLE WEIGHT	27 Lbs/Mft
CAPACITANCE	68 pF/ft Nom.
IMPEDANCE	28 Ohms
TEMPERATURE RATING	75 C / 300 Volt

INDUSTRY STANDARDS

FLAME RATING	Approved For Plenum Use Without Conduit Per NFPA 262 Flame Test
AGENCY APPROVALS	NEC Article 800; UL Listed C(UL)US CMP, RoHS Compliant, Made in the USA



All specifications referenced are nominal measurements unless otherwise noted.



WINDY CITY WIRE • T 800.379.1191 • windycitywire.com

© Windy City Wire, Cable Technology & Products, LLC.
All rights reserved.