PART NUMBER 1802SP-WHT-BLU

UL Listed and Rated Type CMP Multi-Conductor Shielded Plenum Cable

■ 0275/0725 FT ●	SMARTWIRE(TM)	DEVICE/ZONE	A B C D E 0 1 2 3 4 5	6789	K	TECHNOLOGY)
ABLE SPECIFICAT DESCRI		2 twisted Conductor	s Bare Copper, Shielde	ed Plenum	n, UL Listed C(l	JL)US CMP
CONDUCTOR 18 (7/26		6 Bare Copper)				
INSUL	INSULATION Low-Smo					
COLOR	CODE Black/W	Black/White				
LAY L	ENGTH 2.5" LH	L (4.8 TPF)				
S	HIELD Aluminu	ım Mylar				
DRAIN	WIRE 24 AWG	24 AWG 7 Strand Tinned Copper				
J	ACKET Low-Sm	Low-Smoke PVC .018"				
JACKET	COLOR White	White Jacket with Blue Stripe				
MA	RKING SMART	WIRE DEVICE / ZONE N THE USA	A B C D E 0 1 2 3 4	5678	9 18 AWG C	C(UL)US CMP ROHS
OVERALL DIA	METER .158" N	om.				
CABLE W	EIGHT 21 Lbs/	Mft.				
CAPACI	TANCE 68 pF/f	Nom.				
IMPE	DANCE 28 Ohm	IS				
TEMPERATURE R	ATING 0 C to 7	25 C / 300 Volt				

INDUSTRY STANDARDS

FLAME RATING	Approved For Plenum Use Without Conduit Per NFPA 262 Flame Test
AGENCY APPROVALS	NEC Article 800; UL Listed C(UL)US CMP, RoHs Compliant, Made in the USA



All specifications referenced are nominal measurements unless otherwise noted.

WINDY CITY WIRE T 800.379.1191 windycitywire.com
^{© Windy City Wire, Coble Technology & Products, LLC.}
All rights reserved.