PART NUMBER 1802SP-WHT-PUR

UL Listed and Rated Type CMP Multi-Conductor Shielded Plenum Cable

■ 0275/0725 FT ●	SMARTWI	RE(TM)	DEVICE/ZONE	A B C D E O 1 2 3 4	56789		TECHNOLOGY	
ABLE SPECIFICAT								
DESCRI	-			rs Bare Copper, Shield	aed Plenum	i, UL Listed C	(UL)US CMP	
CONDU			Bare Copper)					
INSUL	-		oke PVC .008"					
COLOR		Black/White						
LAY LE	INGTH	2.5" LHL (4.8 TPF)						
S	HIELD	Aluminum Mylar						
DRAIN	WIRE	24 AWG 7 Strand Tinned Copper						
J	ACKET	Low-Smo	oke PVC .018"					
JACKET O	COLOR	White Jacket with Purple Stripe						
MAF	RKING	SMARTWIRE DEVICE / ZONE A B C D E 0 1 2 3 4 5 6 7 8 9 18 AWG C(UL)US CMP ROHS MADE IN THE USA						
OVERALL DIAN	METER	.158" Nom.						
CABLE W	EIGHT	21 Lbs/Mft.						
CAPACI	TANCE	68 pF/ft Nom.						
IMPED	DANCE	28 Ohms						
TEMPERATURE RA	ATING	0 C to 75	5 C / 300 Volt					
NDUSTRY STAND	ARDS							

INDUSTRY STANDARDS

FLAME RATING	Approved For Plenum Use Without Conduit Per NFPA 262 Flame Test
AGENCY APPROVALS	NEC Article 800; UL Listed C(UL)US CMP, RoHs Compliant, Made in the USA



All specifications referenced are nominal measurements unless otherwise noted.

WINDY CITY WIRE T 800.379.1191 windycitywire.com
^{© Windy City Wire, Coble Technology & Products, LLC.}
All rights reserved.