


PART NUMBER 1802SPFA-BLU

UL Listed and Rated Type FPLP Multi-Conductor Shielded Plenum Fire Alarm

■ 0275/0725 FT ● FIRE/LIFE SAFETY CONTROL CABLE INIT/IND DEVICE/ZONE ABCDE0123456789



CABLE SPECIFICATIONS

| | |
|---------------------------|--|
| DESCRIPTION | 18 AWG 2 Conductor Bare Copper, Twisted, Shielded Plenum Fire Alarm, FPLP (UL) |
| CONDUCTOR | 18 (Solid Bare Copper) |
| INSULATION | Low-Smoke PVC .010" |
| COLOR CODE | Black/Red |
| LAY LENGTH | 3" LHL (4 TPF) |
| SHIELD | Aluminum Mylar |
| DRAIN WIRE | 22 AWG Solid Tinned Copper |
| JACKET | Low-Smoke PVC .018" |
| JACKET COLOR | Blue Jacket |
| MARKING | FIRE/LIFE SAFETY CONTROL CABLE INIT. / IND. DEVICE / ZONE A B C D E 0 1 2 3 4 5 6 7 8 9 18 AWG FPLP (UL) ROHS MADE IN THE USA |
| OVERALL DIAMETER | .158" Nom. |
| CABLE WEIGHT | 22 Lbs/Mft. |
| CAPACITANCE | 60 pF/Ft. Nom. |
| IMPEDANCE | 31 Ohms |
| DC RESISTANCE | 6.52 Ohms/Mft @ 20 deg. C |
| TEMPERATURE RATING | 0 C to 75 C / 300 Volt |

INDUSTRY STANDARDS

| | |
|-------------------------|---|
| FLAME RATING | Approved For Plenum Use Without Conduit Per NFPA 262 Flame Test |
| AGENCY APPROVALS | NEC Article 760; FPLP (UL), RoHS Compliant, Made in the USA |



All specifications referenced are nominal measurements unless otherwise noted.



WINDY CITY WIRE • T 800.379.1191 • windycitywire.com

© Windy City Wire, Cable Technology & Products, LLC.
All rights reserved.