PART NUMBER 1803P-WHT-BLU

UL Listed and Rated Type CMP Multi-Conductor Non-Shielded Plenum Cable

■ 0275/0725 FT ●	SMARTWIRE(TM)	DEVICE/ZONE	A B C D E 0 1 2 3	456789				
ABLE SPECIFICAT DESCRI		G 3 Conductor Bare Co	pper, Non-Shielde	d Plenum, UL	Listed C(UL)US	5 CMP		
CONDU	CONDUCTOR 18 (7/26		7/26 Bare Copper)					
INSUL	ATION Low-Sr	noke PVC .008"						
COLOR	CODE Black/W	Black/White/Red						
LAY LE	NGTH 3.25" L	3.25" LHL (approx. 3.7 TPF)						
s	HIELD N/A							
DRAIN	WIRE N/A							
J	ACKET Low-Sr	noke PVC .018"						
JACKET (COLOR White	Jacket with Blue Stripe						
MAI		WIRE DEVICE / ZONE N THE USA	A B C D E 0 1 2	3 4 5 6 7 8 9	18 AWG C(UL)US CMP ROHS		
OVERALL DIA	METER .168" M	om.						
CABLE W	EIGHT 23 Lbs,	Mft.				ß		
CAPACI	TANCE 27 pF/f	t. Nom.		_				
IMPE	DANCE 70 Ohr	is						
TEMPERATURE R	ATING 0 C to	75 C / 300 Volt						

INDUSTRY STANDARDS

FLAME RATING	Approved For Plenum Use Without Conduit Per NFPA 262 Flame Test
AGENCY APPROVALS	NEC Article 800; UL Listed C(UL)US CMP, RoHs Compliant, Made in the USA



All specifications referenced are nominal measurements unless otherwise noted.

WINDY CITY WIRE T 800.379.1191 windycitywire.com
^{© Windy City Wire, Coble Technology & Products, LLC.}
All rights reserved.