PART NUMBER 1803SP-WHT-ORG

UL Listed and Rated Type CMP Multi-Conductor Shielded Plenum Cable

■ 0275/0725 FT ●	SMARTWIRE(TM)	DEVICE/ZONE	A B C D E 0 1 2 3 4 5 6	789	
ABLE SPECIFICAT DESCRI		3 Conductor Bare Co	opper, Shielded Plenum,	UL Listed C(UL))US CL3P
	•	Bare Copper) oke PVC .008"			
COLOR LAY LI		hite/Red IL (approx. 3.7 TPF)	Ш. —		
S DRAIN	HIELD Aluminu WIRE 24 AWG	m Mylar 7 Strand Tinned Cop	pper		
J JACKET (oke PVC .018" acket with Orange St	ripe		
MA		/IRE DEVICE / ZONE I THE USA	A B C D E 0 1 2 3 4 5	6789 18 AV	NG C(UL)US CL3P ROHS
OVERALL DIA					
CAPACI IMPEI	TANCE68 pF/ftDANCE28 Ohm				
TEMPERATURE R		25 C / 300 Volt			

INDUSTRY STANDARDS

FLAME RATING	Approved For Plenum Use Without Conduit Per NFPA 262 Flame Test
AGENCY APPROVALS	NEC Article 800; UL Listed C(UL)US CL3P, RoHs Compliant, Made in the USA



All specifications referenced are nominal measurements unless otherwise noted.

WINDY CITY WIRE T 800.379.1191 windycitywire.com
^{© Windy City Wire, Coble Technology & Products, LLC.}
All rights reserved.