## PART NUMBER 1803SP-WHT-PUR

UL Listed and Rated Type CMP Multi-Conductor Shielded Plenum Cable

■ 0275/0725 FT ●	SMARTWIRE(TM)	DEVICE/ZONE	A B C D E 0 1 2 3	456789		
ABLE SPECIFICAT DESCRII		NG 3 Conductor Bare Co	pper, Shielded Plen	ium, UL List	ed C(UL)US CL	_3P
CONDU	<b>JCTOR</b> 18 (2	/26 Bare Copper)				
INSUL	ATION Low-	Smoke PVC .008"				
COLOR	CODE Black	/White/Red	1.1			
LAY LE	<b>NGTH</b> 3.25	LHL (approx. 3.7 TPF)				
S	<b>HIELD</b> Alum	inum Mylar				
DRAIN	<b>WIRE</b> 24 A	WG 7 Strand Tinned Cop	per			
/נ	ACKET Low-	Smoke PVC .018"				
JACKET C	COLOR Whi	e Jacket with Purple Str	pe			
МАГ		RTWIRE DEVICE / ZONE IN THE USA	A B C D E 0 1 2 3	45678	9 18 AWG C(	(UL)US CL3P ROHS
OVERALL DIAN	METER .168	Nom.				
CABLE W	EIGHT 26 L	os/Mft.				ß
CAPACIT	FANCE 68 p	/ft Nom.		_		
IMPEC	<b>DANCE</b> 28 0	nms				
TEMPERATURE R	ATING 0 C	:o 75 C / 300 Volt				

## INDUSTRY STANDARDS

FLAME RATING	Approved For Plenum Use Without Conduit Per NFPA 262 Flame Test
AGENCY APPROVALS	NEC Article 800; UL Listed C(UL)US CL3P, RoHs Compliant, Made in the USA



All specifications referenced are nominal measurements unless otherwise noted.

