

PART NUMBER 1803SP-WHT

UL Listed and Rated Type CMP Multi-Conductor Shielded Plenum Cable



CABLE SPECIFICATIONS

| | |
|---------------------------|---|
| DESCRIPTION | 18 AWG 3 Conductor Bare Copper, Shielded Plenum, UL Listed C(UL)US CL3P |
| CONDUCTOR | 18 (7/26 Bare Copper) |
| INSULATION | Low-Smoke PVC .008" |
| COLOR CODE | Black/White/Red |
| LAY LENGTH | 3.25" LHL (approx. 3.7 TPF) |
| SHIELD | Aluminum Mylar |
| DRAIN WIRE | 24 AWG 7 Strand Tinned Copper |
| JACKET | Low-Smoke PVC .018" |
| JACKET COLOR | White Jacket |
| MARKING | SMARTWIRE DEVICE / ZONE A B C D E 0 1 2 3 4 5 6 7 8 9 18 AWG C(UL)US CL3P ROHS MADE IN THE USA |
| OVERALL DIAMETER | .168" Nom. |
| CABLE WEIGHT | 26 Lbs/Mft. |
| CAPACITANCE | 68 pF/ft Nom. |
| IMPEDANCE | 28 Ohms |
| TEMPERATURE RATING | 0 C to 75 C / 300 Volt |

INDUSTRY STANDARDS

| | |
|-------------------------|--|
| FLAME RATING | Approved For Plenum Use Without Conduit Per NFPA 262 Flame Test |
| AGENCY APPROVALS | NEC Article 800; UL Listed C(UL)US CL3P, RoHs Compliant, Made in the USA |



All specifications referenced are nominal measurements unless otherwise noted.



WINDY CITY WIRE • T 800.379.1191 • windycitywire.com

© Windy City Wire, Cable Technology & Products, LLC.
All rights reserved.