## PART NUMBER 1803SP-YLW

UL Listed and Rated Type CMP Multi-Conductor Shielded Plenum Cable

■ 0275/0725 FT ●	SMARTWIRE(TM)	DEVICE/ZONE	A B C D E 0 1 2 3 4	56789	SMARTWIR GLA TECHN	
CABLE SPECIFICAT DESCRII	PTION 18 AWG	3 Conductor Bare Co	opper, Shielded Plenu	ım, UL Listed C(	UL)US CL3P	
CONDUCTOR18 (7/26 Bare CoppeINSULATIONLow-Smoke PVC .008						
COLOR LAY LE	· · · ,	Black/White/Red 3.25" LHL (approx. 3.7 TPF)				
S DRAIN		Aluminum Mylar 24 AWG 7 Strand Tinned Copper				
JACKET C		Low-Smoke PVC .018" Yellow Jacket				
	MADE I	SMARTWIRE DEVICE / ZONE A B C D E 0 1 2 3 4 5 6 7 8 9 18 AWG C(UL)US CL3P ROHS MADE IN THE USA				
OVERALL DIAN CABLE W			_		R	
CAPACIT						
TEMPERATURE R	ATING 0 C to	75 C / 300 Volt				

## INDUSTRY STANDARDS

FLAME RATING	Approved For Plenum Use Without Conduit Per NFPA 262 Flame Test
AGENCY APPROVALS	NEC Article 800; UL Listed C(UL)US CL3P, RoHs Compliant, Made in the USA



All specifications referenced are nominal measurements unless otherwise noted.

WINDY CITY WIRE T 800.379.1191 windycitywire.com 
<sup>© Windy City Wire, Coble Technology & Products, LLC.</sup>
All rights reserved.