PART NUMBER 1804P-PUR

UL Listed and Rated Type CMP Multi-Conductor Non-Shielded Plenum Cable

| ■ 0275/0725 FT • | SMARTWIRE(TM) | DEVICE/ZONE | A B C D E 0 1 2 3 4 5 6 | 789 | SMARTWIRE GLIDE TECHNOLOGY | |
|------------------|----------------------|--------------------------------|---------------------------|-----------------------|----------------------------------|--|
| CABLE SPECIFICAT | | 4 Conductor Bare C | Copper, Non-Shielded Plei | num, UL Listed C(UL)U | IS CMP | |
| CONDU | | 18 (7/26 Bare Copper) | | | | |
| INSULA | • | Low-Smoke PVC .008" | | | | |
| COLOR | CODE Black/W | Black/White/Red/Green | | | | |
| LAY LE | | 3.5" LHL (approx. 3.4 TPF) | | | | |
| SI | HIELD N/A | N/A N/A | | | | |
| DRAIN | WIRE N/A | | | | | |
| JA | ACKET Low-Sm | oke PVC .018" | F 1 | | | |
| JACKET C | OLOR Purple | Jacket | | | | |
| MAR | | VIRE DEVICE / ZON N THE USA | E A B C D E 0 1 2 3 4 5 | 6789 18 AWG C(| (UL)US CMP ROHS | |
| OVERALL DIAM | IETER .184" N | om. | | | | |
| CABLE WE | EIGHT 32 Lbs/ | 32 Lbs/Mft. | | | | |
| CAPACIT | ANCE 26 pF/F | Nom | | | | |
| IMPED | ANCE 72 Ohm | s | | | | |
| DC RESIST | ANCE 6.66 Oh | 6.66 Ohms/Mft. maximum @ 20 C | | | | |
| TEMPERATURE RA | TING 0 C to 7 | 5 C / 300 Volt | | | | |
| | | | | | | |
| INDUSTRY STAND | ARDS | | | | | |

FLAME RATING

Approved For Plenum Use Without Conduit Per NFPA 262 Flame Test NEC Article 800; UL Listed C(UL)US CMP, RoHs Compliant, Made in the USA



All specifications referenced are nominal measurements unless otherwise noted.

