## **PART NUMBER 1804P-TSTAT-WHT**

UL Listed and Rated Type CMP Multi-Conductor Non-Shielded Plenum Thermostat Cable

	0						GLIDE
■ 0275/0725 FT ●	SMARTW	IRE(TM)	DEVICE/ZONE	A  B  C  D  E  0  1  2  3  4  5	6789		TECHNOLOGY
ABLE SPECIFICAT	TIONS						
DESCRI		18 AWG 4	Conductor Bare C	opper, Non-Shielded Ple	enum, UL l	isted C(UL)	)US CMP
COND	UCTOR	18 (Solid	Bare Copper)				
INSUL	ATION	Low-Smo	ke PVC .008"				
COLOF	R CODE	Black/Wh	ite/Red/Green				
S	HIELD	N/A					
DRAIN	I WIRE	N/A					
ſ	ACKET	Low-Smo	ke PVC .018"	4 K			
JACKET	COLOR	White Ja	cket				
MA	RKING	SMARTWI		E A B C D E 0 1 2 3 4 5	56789	18 AWG	C(UL)US CMP ROHS
OVERALL DIA	METER	.184" Nor	n				
CABLE W	EIGHT	35 Lbs/Mi	ft.				
CAPACI	TANCE	22 pF/Ft.	Nom.				ß
IMPE	DANCE	86 Ohms			_		
TEMPERATURE R	ATING	0 C to 75	5 C / 300 Volt				
INDUSTRY STAND	ARDS						
FLAME R	ATING	Approved	For Plenum Use W	ithout Conduit Per NFPA	262 Flam	e Test	

NEC Article 800; UL Listed C(UL)US CMP, RoHS Compliant, Made in the USA

AGENCY APPROVALS



All specifications referenced are nominal measurements unless otherwise noted.

