PART NUMBER 1804P-WHT

UL Listed and Rated Type CMP Multi-Conductor Non-Shielded Plenum Cable

							SMARTWIRE	
■ 0275/0725 FT ●	SMARTW	IRE(TM)	DEVICE/ZONE	A B C D E 0 1 2 3 4 5	6789		TECHNOLOGY	
ABLE SPECIFICA	TIONS							
DESCRIPTION		18 AWG 4 Conductor Bare Copper, Non-Shielded Plenum, UL Listed C(UL)US CMP						
CONDUCTOR		18 (7/26 Bare Copper)						
INSU	LATION	Low-Smc	ow-Smoke PVC .008"					
COLO	OR CODE	Black/Wh	iite/Red/Green	111				
LAY	LENGTH	3.5" LHL	(approx. 3.4 TPF)	- Mar 1997				
	SHIELD	N/A						
DRAI	N WIRE	N/A		6 N				
	JACKET	Low-Smo	ke PVC .018"					
JACKET	COLOR	White Ja	cket					
M.	ARKING	SMARTW MADE IN	IRE DEVICE / ZON THE USA	E A B C D E 0 1 2 3 4 !	56789 1	8 AWG C(UL)US CMP ROHS	
OVERALL DI	AMETER	.184" No	m.					
CABLE	WEIGHT	32 Lbs/M	ft.				R	
САРАС	TANCE	26 pF/Ft.	Nom.					
IMP	EDANCE	72 Ohms						
DC RESI	STANCE	6.66 Ohn	ns/Mft. maximum @	a) 20 C				
TEMPERATURE	RATING	0 C to 75	C / 300 Volt					
NDUSTRY STAN	DARDS							
FLAME	RATING	Approved For Plenum Use Without Conduit Per NFPA 262 Flame Test						

AGENCY APPROVALS

NEC Article 800; UL Listed C(UL)US CMP, RoHs Compliant, Made in the USA

All specifications referenced are nominal measurements unless otherwise noted.

WINDY CITY WIRE T 800.379.1191 windycitywire.com
^{© Windy City Wire, Coble Technology & Products, LLC.}
All rights reserved.