PART NUMBER 1804P-YLW

UL Listed and Rated Type CMP Multi-Conductor Non-Shielded Plenum Cable

								SMARTWIRE	ne
■ 0275/0725 FT ●	SMARTWI	RE(TM)	DEVICE/ZONE	ABCDE	0123456	789		ТЕСНКО	LOGY
ABLE SPECIFICA			Conductor Poro C	Connor Non (Chielded Die		atod C(UU)		
DESCRIPTION		18 AWG 4 Conductor Bare Copper, Non-Shielded Plenum, UL Listed C(UL)US CMP							
CONDUCTOR		18 (7/26 Bare Copper)							
INSULATION		Low-Smoke PVC .008"							
COLO	R CODE		te/Red/Green						
LAY L	LENGTH	3.5" LHL (approx. 3.4 TPF)							
5	SHIELD	N/A							
DRAII	N WIRE	N/A		6 K.					
:	JACKET	Low-Smol	ke PVC .018"						
JACKET	COLOR	Yellow Ja	cket	6 - N					
MA	ARKING	SMARTWI MADE IN	RE DEVICE / ZON THE USA	EABCDE	012345	6789	18 AWG C	(UL)US CMP R	OHS
OVERALL DIA	AMETER	.184" Non	٦.						
CABLE V	VEIGHT	32 Lbs/Mf	t.						
CAPAC	ITANCE	26 pF/Ft.	Nom.						
IMPE	DANCE	72 Ohms							
DC RESIS	STANCE	6.66 Ohm	s/Mft. maximum @	@ 20 C					
TEMPERATURE F	RATING	0 C to 75	C / 300 Volt						
INDUSTRY STAN	DARDS								
FLAME F	RATING	Approved	For Plenum Use W	Vithout Condu	it Per NFPA	262 Flame	e Test	-	

AGENCY APPROVALS

Approved For Plenum Use Without Conduit Per NFPA 262 Flame Test NEC Article 800; UL Listed C(UL)US CMP, RoHs Compliant, Made in the USA



All specifications referenced are nominal measurements unless otherwise noted.

WINDY CITY WIRE · T 800.379.1191 · windycitywire.com · [©] Windy City Wire, Cable Technology & Products, LLC. All rights reserved.