## PART NUMBER 1804SP-ORG

UL Listed and Rated Type CMP Multi-Conductor Shielded Plenum Cable

■ 0275/0725 FT ●	SMARTW	IRE(TM)	DEVICE/ZONE	A B C D E 0 1 2 3	456789		SMARTWIRE GLIDE
CABLE SPECIFICAT	IONS						
DESCRI	PTION	18 AWG 4	4 twisted Conducto	or Bare Copper, Shie	lded Plenum	, UL Listed C(UL	)US CMP
CONDU	UCTOR	18 (7/26 Bare Copper)					
INSUL	ATION	Low-Smoke PVC .008"					
COLOR		Black/Wh	ite/Red/Green				
LAY LE	ENGTH	3.5" LHL	(3.4 TPF)				
S	HIELD	Aluminun	n Mylar				
DRAIN	WIRE	24 AWG	7 Strand Tinned Co	pper			
J	ACKET	Low-Smo	ke PVC .018"				
JACKET (	COLOR	Orange 2	lacket	6 B			
MAI	RKING	SMARTW MADE IN		EABCDE012	3 4 5 6 7 8	9 18 AWG C(	UL)US CMP ROHS
OVERALL DIA	METER	.184" Noi	n.				
CABLE W	EIGHT	37 Lbs/M	ft.				
CAPACI	TANCE	68 pF/ft I	Nom.				
IMPE	DANCE	28 Ohms					
DC RESIS	TANCE	6.66 Ohn	ns/Mft. maximum @	@ 20 C			
TEMPERATURE R	ATING	0 C to 7	5 C / 300 Volt				

## **INDUSTRY STANDARDS**

FLAME RATINGApproved For Plenum Use Without Conduit Per NFPA 262 Flame TestAGENCY APPROVALSNEC Article 800; UL Listed C(UL)US CMP, RoHs Compliant, Made in the USA



All specifications referenced are nominal measurements unless otherwise noted.

