## **PART NUMBER 1804SPFA-RED**

UL Listed and Rated Type FPLP Multi-Conductor Shielded Plenum Fire Alarm

■ 0275/0725 FT ● FIRE/LIFE SAFETY CONTROL CABLE INIT/IND DEVICE/ZONE ABCDE0123456789





## **CABLE SPECIFICATIONS**

**DESCRIPTION** 18 AWG 4 Conductor Bare Copper, Shielded Plenum Fire Alarm, FPLP (UL)

CONDUCTOR 18 (Solid Bare Copper)

INSULATION Low-Smoke PVC .010"

COLOR CODE Black/Red/Brown/Blue

SHIELD Aluminum Mylar

**DRAIN WIRE** 22 AWG Solid Tinned Copper

JACKET Low-Smoke PVC .018"

JACKET COLOR Red Jacket

MARKING FIRE/LIFE SAFETY CONTROL CABLE INIT. / IND. DEVICE / ZONE A B C D E 0 1 2 3 4 5 6 7 8 9

18 AWG FPLP (UL) ROHS MADE IN THE USA

OVERALL DIAMETER .184" Nom.

CABLE WEIGHT 35 Lbs/Mft.

**CAPACITANCE** 60 pF/Ft. Nom.

IMPEDANCE 31 Ohms

**TEMPERATURE RATING** 0 C to 75 C / 300 Volt

**INDUSTRY STANDARDS** 

**FLAME RATING** Approved For Plenum Use Without Conduit Per NFPA 262 Flame Test

AGENCY APPROVALS NEC Article 760; FPLP (UL), RoHS Compliant, Made in the USA





All specifications referenced are nominal measurements unless otherwise noted.