PART NUMBER 1806P-TSTAT-WHT

UL Listed and Rated Type CMP Multi-Conductor Non-Shielded Plenum Thermostat Cable

■ 0275/0725 FT ●	SMARTWI	RE(TM)	DEVICE/ZONE	ABCDE012	23456789	K	GLID TECHNOLO	G Y
ABLE SPECIFICA								
DESCRI	_		5 Conductor Bare C	opper, Non-Shiel	ded Plenum, l	JL Listed C(UL)	US CMP	
COND	UCTOR	18 (Solid	Bare Copper)					
INSUL	ATION	Low-Smo	ke PVC .008"					
COLOF	R CODE	Black/Wh	ite/Red/Green/Brov	wn/Blue				
S	SHIELD	N/A						
DRAIN	N WIRE	N/A						
E	JACKET	Low-Smo	ke PVC .018"	6 N				
JACKET	COLOR	White Ja	cket					
MA	RKING	SMARTWI MADE IN	IRE DEVICE / ZONE	EABCDE01	2345678	9 18 AWG (C(UL)US CMP ROH	5
OVERALL DIA	METER	.208" Nor	n					
CABLE W	/EIGHT	55 Lbs/M	ft.					
CAPACI	TANCE	22 pF/Ft.	Nom.					
IMPE	DANCE	86 Ohms						
TEMPERATURE R	ATING	0 C to 75	5 C / 300 Volt					
NDUSTRY STAND	DARDS							

INDUSTRY STANDARDS

WINDY CIT

FLAME RATINGApproved For Plenum Use Without Conduit Per NFPA 262 Flame TestAGENCY APPROVALSNEC Article 800; UL Listed C(UL)US CMP, RoHS Compliant, Made in the USA



All specifications referenced are nominal measurements unless otherwise noted.

WIRE • T 800.379.1191 • windycitywire.com • [©] Windy City Wire, Cable Technology & Products, LLC. All rights reserved.