PART NUMBER 1806SP-WHT-BLK

UL Listed and Rated Type CMP Multi-Conductor Shielded Plenum Cable

| ■ 0275/0725 FT ● | SMARTWIRE(TM) | DEVICE/ZONE A B C D E 0 1 2 3 4 5 6 7 8 9 |
|------------------|---------------------|--|
| ABLE SPECIFICA | | |
| DESCR | IPTION 18 A | WG 6 Conductor Bare Copper, Shielded Plenum, UL Listed C(UL)US CMP |
| CONI | DUCTOR 18 (7 | 7/26 Bare Copper) |
| INSU | LATION Low- | Smoke PVC .008" |
| COLO | R CODE Black | k/Red/White/Green/Brown/Blue |
| | SHIELD Alum | ninum Mylar |
| DRAI | N WIRE 24 A | WG 7 Strand Tinned Copper |
| | JACKET Low- | Smoke PVC .018" |
| JACKET | COLOR White | te Jacket with Black Stripe |
| M | | RTWIRE DEVICE / ZONE A B C D E 0 1 2 3 4 5 6 7 8 9 18 AWG C(UL)US CMP ROHS E IN THE USA |
| OVERALL DI | AMETER .208 | " Nom. |
| CABLE \ | NEIGHT 47 Lt | bs/Mft. |
| САРАС | ITANCE 68 pl | F/Ft. Nom. |
| IMPI | EDANCE 28 0 | hms |
| TEMPERATURE | RATING 0 C | to 75 C / 300 Volt |
| | | |

INDUSTRY STANDARDS

WINDY CITY

 FLAME RATING
 Approved For Plenum Use Without Conduit Per NFPA 262 Flame Test

 AGENCY APPROVALS
 NEC Article 800; UL Listed C(UL)US CMP, RoHS Compliant, Made in the USA



All specifications referenced are nominal measurements unless otherwise noted.

WIRE • T 800.379.1191 • windycitywire.com • [©] Windy City Wire, Cable Technology & Products, LLC. All rights reserved.