## PART NUMBER 1806SP-WHT-RED

UL Listed and Rated Type CMP Multi-Conductor Shielded Plenum Cable

■ 0275/0725 FT ●	SMARTWIRE(TM)		DEVICE/ZONE	ABCDE	0 1 2 3 4 5 6 7	89			HNOLO	G Y
ABLE SPECIFICAT	IONS									
DESCRI	PTION	18 AWG	6 Conductor Bare (	Copper, Shield	ed Plenum, U	JL Liste	d C(UL)US	СМР		
CONDU	JCTOR	18 (7/26	Bare Copper)							
INSUL	ATION	Low-Sm	oke PVC .008"							
COLOR	CODE	Black/Re	d/White/Green/Bro	wn/Blue						
S	HIELD	Aluminu	n Mylar	. H. L						
DRAIN	WIRE	24 AWG	7 Strand Tinned Co	opper						
J	ACKET	Low-Sm	oke PVC .018"	d 14.						
JACKET (	COLOR	White Ja	acket with Red Strip	be						
MAI	RKING		IRE DEVICE / ZON THE USA	EABCDE(	0 1 2 3 4 5 6	789	18 AWG	C(UL)US	CMP ROF	IS
OVERALL DIA	METER	.208" No	m.							
CABLE W	EIGHT	47 Lbs/M	lft.							
CAPACI	TANCE	68 pF/Ft. Nom.								
IMPE	DANCE	28 Ohms								
TEMPERATURE R	ATING	0 C to 7	5 C / 300 Volt							

## **INDUSTRY STANDARDS**

WINDY CITY

 FLAME RATING
 Approved For Plenum Use Without Conduit Per NFPA 262 Flame Test

 AGENCY APPROVALS
 NEC Article 800; UL Listed C(UL)US CMP, RoHS Compliant, Made in the USA



All specifications referenced are nominal measurements unless otherwise noted.

WIRE • T 800.379.1191 • windycitywire.com • <sup>©</sup> Windy City Wire, Cable Technology & Products, LLC. All rights reserved.