PART NUMBER 1808P-PUR

UL Listed and Rated Type CMP Multi-Conductor Non-Shielded Plenum Cable

■ 0275/0725 FT ●	SMARTW	IRE(TM)	DEVICE/ZONE	A B C D E 0 1 2 3 4	56789		SMARTWIRE GLIDE
							TECHNOLOGI
CABLE SPECIFICA	TIONS						
	IPTION	18 AWG	8 Conductor Bare C	Copper, Non-Shielded	Plenum, Ul	Listed C(UL)U	IS CMP
COND	DUCTOR	18 (7/26	Bare Copper)				
INSU	LATION	Low-Smoke PVC .008"					
COLO	R CODE	Black/White/Red/Green/Brown/Blue/Orange/Yellow					
LAY L	ENGTH	3.75" LHL (approx. 3.2 TPF)					
:	SHIELD	N/A					
DRAI	N WIRE	N/A		4 K			
	JACKET	Low-Smo	oke PVC .018"				
JACKET	COLOR	Purple J	acket				
MA	ARKING		IRE DEVICE / ZON THE USA	E A B C D E 0 1 2 3	456789	9 18 AWG C	(UL)US CMP ROHS
OVERALL DIA	METER	.234" No	m.				
CABLE V	VEIGHT	62 Lbs/№	lft.				R
CAPAC	ITANCE	27 pF/Ft	. Nom.		_		
IMPE	DANCE	70 Ohms	;				
DC RESIS	STANCE	6.66 Ohr	ms/1000ft max @ 2	0 C			
TEMPERATURE F	RATING	0 C to 7	5 C / 300 Volt				

INDUSTRY STANDARDS

FLAME RATINGApproved For Plenum Use Without Conduit Per NFPA 262 Flame TestAGENCY APPROVALSNEC Article 800; UL Listed C(UL)US CMP, RoHs Compliant, Made in the USA



All specifications referenced are nominal measurements unless otherwise noted.

