PART NUMBER 1808P-WHT

UL Listed and Rated Type CMP Multi-Conductor Non-Shielded Plenum Cable

■ 0275/0725 FT ●	SMARTW	'IRE(TM)	DEVICE/ZONE	A B C D E 0 1 2 3 4 5	6789	SMARTWIRE GLIDE TECHNOLOGY	
ABLE SPECIFICA	TIONS						
DESCR	IPTION	18 AWG	8 Conductor Bare C	Copper, Non-Shielded Pl	enum, UL Listed	C(UL)US CMP	
CONDUCTOR		18 (7/26 Bare Copper)					
INSULATION		Low-Smoke PVC .008"					
COLO	R CODE	Black/Wh	Black/White/Red/Green/Brown/Blue/Orange/Yellow				
LAYI	LENGTH	3.75" LH	L (approx. 3.2 TPF)				
	SHIELD	N/A					
DRAI	N WIRE	N/A		4 K			
	JACKET	Low-Smo	oke PVC .018"				
JACKET	COLOR	White Ja	cket				
M	ARKING		IRE DEVICE / ZON THE USA	E A B C D E 0 1 2 3 4	56789 18A	AWG C(UL)US CMP ROHS	
OVERALL DI	AMETER	.234" No	m.				
CABLE V	NEIGHT	62 Lbs/M	ft.				
САРАС	ITANCE	27 pF/Ft.	Nom.				
IMPI	EDANCE	70 Ohms					
DC RESIS	STANCE	6.66 Ohr	ns/1000ft max @ 2	0 C			
TEMPERATURE	RATING	0 C to 7	5 C / 300 Volt				
NDUSTRY STAN	DARDS						

FLAME RATING

WINDY CIT

Approved For Plenum Use Without Conduit Per NFPA 262 Flame Test AGENCY APPROVALS NEC Article 800; UL Listed C(UL)US CMP, RoHs Compliant, Made in the USA



All specifications referenced are nominal measurements unless otherwise noted.

WIRE • T 800.379.1191 • windycitywire.com • [©] WindyCityWire, Cable Technology & Products, LLC. All rights reserved.