PART NUMBER 1810P-WHT-500

UL Listed and Rated Type CMP Multi-Conductor Non-Shielded Plenum Cable

■ 0275/0725 FT ●	SMARTW	'IRE(TM)	DEVICE/ZONE	A B C D E 0 1 2 3 4 5 6 5	789	SMARTWIRE GLIDE TECHNOLOGY	
ABLE SPECIFICA							
	RIPTION			Copper, Non-Shielded Ple	num, UL Listed C(UL	.)US CMP	
			Bare Copper)				
			Low-Smoke PVC .008"				
COLC	R CODE Black/White/Red/Green/Brown/Blue/Orange/Yellow/Purple/Gray						
LAY	LENGTH	4" LHL (a	ipprox. 3 TPF)	- Mar 1997			
	SHIELD	N/A					
DRAI	IN WIRE	N/A		6 N			
	JACKET	Low-Smo	oke PVC .018"				
JACKET	T COLOR	White Ja	cket				
м	ARKING	SMARTWIRE DEVICE / ZONE A B C D E 0 1 2 3 4 5 6 7 8 9 18 AWG C(UL)US CMP ROHS MADE IN THE USA					
OVERALL DI	AMETER	.258" Nom.					
CABLE	WEIGHT	75 Lbs/Mft.					
САРАС		27 pF/Ft. Nom.					
IMP	EDANCE	70 Ohms					
TEMPERATURE	RATING	0 C to 7	5 C / 300 Volt				
INDUSTRY STAN	IDARDS						

INDUSTRY STANDARDS

FLAME RATING	Approved For Plenum Use Without Conduit Per NFPA 262 Flame Test
AGENCY APPROVALS	NEC Article 800; UL Listed C(UL)US CMP, RoHs Compliant, Made in the USA



All specifications referenced are nominal measurements unless otherwise noted.

