PART NUMBER 1812P-WHT-500

UL Listed and Rated Type CMP Multi-Conductor Non-Shielded Plenum Cable

■ 0275/0725 FT •

SMARTWIRE(TM)

DEVICE/ZONE

ABCDE0123456789





CABLE SPECIFICATIONS

DESCRIPTION 18 AWG 12 Conductor Bare Copper, Non-Shielded Plenum, UL Listed C(UL)US CMP

CONDUCTOR 18 (7/26 Bare Copper)

INSULATION Low-Smoke PVC .008"

COLOR CODE Black/White/Red/Green/Brown/Blue/Orange/Yellow/Purple/Gray/Pink/Tan

LAY LENGTH 4.5" LHL (approx. 2.6 TPF)

SHIELD N/A

DRAIN WIRE N/A

JACKET Low-Smoke PVC .018"

JACKET COLOR White Jacket

MARKING SMARTWIRE DEVICE / ZONE A B C D E 0 1 2 3 4 5 6 7 8 9 18 AWG C(UL)US CMP ROHS

MADE IN THE USA

OVERALL DIAMETER .279" Nom.

CABLE WEIGHT 94 Lbs/Mft.

CAPACITANCE 27 pF/Ft. Nom.

IMPEDANCE 70 Ohms

TEMPERATURE RATING 0 C to 75 C / 300 Volt

INDUSTRY STANDARDS

FLAME RATING Approved For Plenum Use Without Conduit Per NFPA 262 Flame Test

AGENCY APPROVALS NEC Article 800; UL Listed C(UL)US CMP, RoHs Compliant, Made in the USA





