PART NUMBER 1812P-WHT

UL Listed and Rated Type CMP Multi-Conductor Non-Shielded Plenum Cable

■ 0275/0725 FT ●	SMARTWIRE(TM)	DEVICE/ZONE	A B C D E 0 1 2 3 4 5 6 7 8 9	SMARTWIRE GLA TECHNO		
ABLE SPECIFICA						
DESCRI		18 AWG 12 Conductor Bare Copper, Non-Shielded Plenum, UL Listed C(UL)US CMP				
COND	UCTOR 18 (7/2	18 (7/26 Bare Copper)				
INSUL	ATION Low-Sr	Low-Smoke PVC .008"				
COLOR CODE Blac		Black/White/Red/Green/Brown/Blue/Orange/Yellow/Purple/Gray/Pink/Tan				
LAY LENGTH 4.5"		4.5" LHL (approx. 2.6 TPF)				
S	SHIELD N/A					
DRAIN	NWIRE N/A		A 14			
C	IACKET Low-Sr	noke PVC .018"				
JACKET	COLOR White	Jacket				
MA		WIRE DEVICE / ZONE N THE USA	E A B C D E 0 1 2 3 4 5 6 7 8	9 18 AWG C(UL)US CMP	ROHS	
OVERALL DIA	. METER .279" r	lom.				
CABLE W	EIGHT 94 Lbs	'Mft.				
CAPACI	TANCE 27 pF/	t. Nom.				
IMPE	DANCE 70 Ohr	าร				
TEMPERATURE R	ATING 0 C to	75 C / 300 Volt				

INDUSTRY STANDARDS

FLAME RATING	Approved For Plenum Use Without Conduit Per NFPA 262 Flame Test
AGENCY APPROVALS	NEC Article 800; UL Listed C(UL)US CMP, RoHs Compliant, Made in the USA



All specifications referenced are nominal measurements unless otherwise noted.

WINDY CITY WIRE T 800.379.1191 windycitywire.com
^{© Windy City Wire, Coble Technology & Products, LLC.}
All rights reserved.