PART NUMBER 181PRSP-BAC-TR-ORG







CABLE SPECIFICATIONS

DESCRIPTION 18 AWG 1 Pair Tinned Copper Shielded, UL Listed C(UL)US CMP

CONDUCTOR 18AWG (19X.0092) Tinned Copper

INSULATION FEP

COLOR CODE Black/White

> SHIELD Aluminum Mylar

DRAIN WIRE 22 AWG 7 Strand Tinned Copper

> JACKET Low-Smoke PVC .018"

JACKET COLOR Orange Jacket

> SMARTWIRE[TM] A B C D E 0 1 2 3 4 5 6 7 8 9 18 AWG C(UL)US CMP ROHS MADE IN THE MARKING

> > USA

OVERALL DIAMETER .190" Nom.

> CABLE WEIGHT 24 Lbs/Mft.

25 pF/Ft. Nom. CAPACITANCE

IMPEDANCE 57 Ohms

TEMPERATURE RATING 75 C / 300 Volt

INDUSTRY STANDARDS

FLAME RATING Approved For Plenum Use Without Conduit Per NEC Article 800, NFPA 262 Flame Test

AGENCY APPROVALS NEC Article 800; UL Listed C(UL)US CMP, RoHS Compliant, Made in the USA







All specifications referenced are nominal measurements unless otherwise noted.