

PART NUMBER 182PREPSP-WHT

UL Listed and Rated Type CMP Multi-Pair Each Pair Shielded Plenum Cable



CABLE SPECIFICATIONS

DESCRIPTION	18 AWG 2 Pair Bare Copper, Individually Shielded Plenum, UL Listed C(UL)US CMP
CONDUCTOR	18 (7/26 Bare Copper)
INSULATION	Low-Smoke PVC .008"
COLOR CODE	Black/Red, White/Green
LAY LENGTH	Individual Pairs: 3" lay Overall Assembly: 3" lay (4 TPF)
SHIELD	Each Pair Aluminum Mylar Foil - Foil In
DRAIN WIRE	2 Separate Drains: 24 AWG 7 Strand Tinned Copper
JACKET	Low-Smoke PVC .018"
JACKET COLOR	White Jacket
MARKING	SMARTWIRE DEVICE / ZONE A B C D E 0 1 2 3 4 5 6 7 8 9 18 AWG C(UL)US CMP ROHS MADE IN THE USA
OVERALL DIAMETER	.195" Nom.
CABLE WEIGHT	35 Lbs/Mft.
CAPACITANCE	68 pF/ft Nom.
IMPEDANCE	28 Ohms
TEMPERATURE RATING	0 C to 75 C / 300 Volt

INDUSTRY STANDARDS

FLAME RATING	Approved For Plenum Use Without Conduit Per NFPA 262 Flame Test
AGENCY APPROVALS	NEC Article 800; UL Listed C(UL)US CMP, RoHS Compliant, Made in the USA



All specifications referenced are nominal measurements unless otherwise noted.



WINDY CITY WIRE • T 800.379.1191 • windycitywire.com

© Windy City Wire, Cable Technology & Products, LLC.
All rights reserved.