

PART NUMBER 2002S-GRY


UL Listed and Rated Type CMR Multi-Conductor Shielded Non-Plenum Cable

■ 0275/0725 FT ●

SMARTWIRE(TM)

DEVICE/ZONE

A B C D E 0 1 2 3 4 5 6 7 8 9



CABLE SPECIFICATIONS

DESCRIPTION	20 AWG 2 Conductor Bare Copper, Shielded Non-Plenum, UL Listed C(UL)US CMR
CONDUCTOR	20 (7/28 Bare Copper)
INSULATION	PVC .008"
COLOR CODE	Black/White
LAY LENGTH	2.75" LHL (approx. 4.3 TPF)
SHIELD	Aluminum Mylar
DRAIN WIRE	24 AWG 7 Strand Tinned Copper
JACKET	PVC .018"
JACKET COLOR	Gray Jacket
MARKING	SMARTWIRE DEVICE / ZONE A B C D E 0 1 2 3 4 5 6 7 8 9 20 AWG C(UL)US CMR 75C ROHS MADE IN USA
OVERALL DIAMETER	.140" Nom.
CABLE WEIGHT	14 Lbs/Mft.
CAPACITANCE	60 pF/Ft. Nom.
IMPEDANCE	31 Ohms
TEMPERATURE RATING	0 C to 75 C / 300 Volt

INDUSTRY STANDARDS

AGENCY APPROVALS NEC Article 800; UL Listed C(UL)US CMR, RoHS Compliant, Made in the USA



All specifications referenced are nominal measurements unless otherwise noted.



WINDY CITY WIRE • T 800.379.1191 • windycitywire.com

© Windy City Wire, Cable Technology & Products, LLC.
All rights reserved.