PART NUMBER 2003SP-WHT-GRN

UL Listed and Rated Type CMPMulti-Conductor Shielded Plenum Cable

■ 0275/0725 FT ●	SMARTWIRE(TM)	DEVICE/ZONE	A B C D E 0 1 2 3	456789		GLIDE,
ABLE SPECIFICAT DESCRI		3 Conductor Twisted	Bare Copper, Shie	elded Plenun	n, UL Listed C((UL)US CMP
CONDUCTOR 20 (7/28		28 Bare Copper)				
INSUL	ATION Low-Sr	noke PVC .008"				
COLOR	CODE Black/V	/hite/Red				
LAY LE	NGTH 2.75" L	HL (approx. 4.36 TPF)	- H.			
S	HIELD Alumin	ım Mylar				
DRAIN	WIRE 24 AWG	24 AWG 7 Strand Tinned Copper				
J	ACKET Low-Sr	noke PVC .018"				
JACKET (COLOR White	White Jacket with Green Stripe				
MAI		WIRE DEVICE / ZONE N THE USA	A B C D E 0 1 2	3 4 5 6 7 8	9 20 AWG	C(UL)US CMP ROHS
OVERALL DIA	METER .149" N	om.				
CABLE W	EIGHT 20 Lbs/	Mft.				ß
CAPACI	TANCE 60 pF/f	60 pF/ft Nom. 31 Ohms				
IMPE	DANCE 31 Ohn					
TEMPERATURE R	ATING 0 C to	75 C / 300 Volt				

INDUSTRY STANDARDS

FLAME RATING	Approved For Plenum Use Without Conduit Per NFPA 262 Flame Test
AGENCY APPROVALS	NEC Article 800; UL Listed C(UL)US CMP, RoHs Compliant, Made in the USA



All specifications referenced are nominal measurements unless otherwise noted.

