PART NUMBER 2005SP-WHT

UL Listed and Rated Type CMP Multi-Conductor Shielded Plenum Cable

■ 0275/0725 FT ●	SMARTWIRE(TM)	DEVICE/ZONE	A B C D E 0 1 2 3 4 5 6 7 8 9		SMARTWIRE GLADE	
ABLE SPECIFICA DESCR		G 5 Conductor Bare Co	pper, Shielded Plenum, UL Li	sted C(UL)US CM	IP	
CONDUCTOR 20		20 (7/28 Bare Copper)				
INSU	LATION Low-Si	noke PVC .008"				
COLOR CODE Black/W		Vhite/Red/Green/Brow	'n			
LAY L	ENGTH 2.75"	HL (approx. 4.36 TPF)	11. A Contract of the second sec			
5	SHIELD Alumir	um Mylar				
DRAII	N WIRE 24 AW	G 7 Strand Tinned Cop	per			
:	JACKET Low-St	noke PVC .018"				
JACKET	COLOR White	White Jacket				
MA		WIRE DEVICE / ZONE IN THE USA	A B C D E 0 1 2 3 4 5 6 7 8	3 9 20 AWG C((UL)US CMP ROHS	
OVERALL DIA	METER .172"	lom.				
CABLE W	VEIGHT 29 Lbs	/Mft.			Ø	
CAPAC	TANCE 60 pF/	t Nom.				
IMPE	DANCE 31 Ohr	ns				
TEMPERATURE F	RATING 0 C to	75 C / 300 Volt				

INDUSTRY STANDARDS

FLAME RATING	Approved For Plenum Use Without Conduit Per NFPA 262 Flame Test
AGENCY APPROVALS	NEC Article 800; UL Listed C(UL)US CMP, RoHs Compliant, Made in the USA



All specifications referenced are nominal measurements unless otherwise noted.

WINDY CITY WIRE T 800.379.1191 windycitywire.com
^{© Windy City Wire, Coble Technology & Products, LLC.}
All rights reserved.