

PART NUMBER 202PRP-1PRS-WHT

UL Listed and Rated Type CMP Multi-Pair 1 Pair Shielded Plenum Cable

■ 0275/0725 FT ●

SOUND/INTERCOM CABLE

A B C D E 0 1 2 3 4 5 6 7 8 9



CABLE SPECIFICATIONS

DESCRIPTION	20 AWG 2 Pair Bare Copper, 1 Pair Shielded Plenum, UL Listed C(UL)US CMP	
CONDUCTOR	20 (7 Strand Bare Copper)	
INSULATION	Low-Smoke PVC .008" Nom.	
COLOR CODE	Pair 1: Black/Red; Pair 2: White/Green	
SHIELD	Pair 1: O/A Foil; Pair 2: N/A	
DRAIN WIRE	Pair 1: 24 AWG Stranded Tinned Copper; Pair 2: N/A	
JACKET	Low-Smoke PVC .018" Nom.	
JACKET COLOR	Blue Jacket	
MARKING	SOUND / INTERCOM CABLE A B C D E 0 1 2 3 4 5 6 7 8 9 20 AWG 1P SHIELDED + 20 AWG 1P NO SHIELD C(UL)US CMP ROHS MADE IN THE USA	
OVERALL DIAMETER	.218" Nom.	
CABLE WEIGHT	25 Lbs/Mft.	
CAPACITANCE	OAS: 60 pF/Ft. Nom.; UNS: 25 pF/Ft. Nom.	
IMPEDANCE	OAS: 31 Ohms; UNS: 75 Ohms	
TEMPERATURE RATING	0 C to 75 C / 300 Volt	

INDUSTRY STANDARDS

FLAME RATING	Approved For Plenum Use Without Conduit Per NFPA 262 Flame Test
AGENCY APPROVALS	NEC Article 800; UL Listed C(UL)US CMP, RoHS Compliant, Made in the USA



All specifications referenced are nominal measurements unless otherwise noted.



WINDY CITY WIRE • T 800.379.1191 • windycitywire.com

© Windy City Wire, Cable Technology & Products, LLC.
All rights reserved.