PART NUMBER 22-2PREPSP-BLK

UL Listed and Rated Type CMP Multi-Pair Each Pair Shielded Plenum Cable

CABLE SPECIFICATIONS

DESCRIPTION	22 AWG 2 Pair Bare Copper, Individually Shielded Plenum, UL Listed C(UL)US CMP
CONDUCTOR	22 (7/30 Bare Copper)
INSULATION	Low-Smoke PVC .008"
COLOR CODE	Black/Red, White/Green
SHIELD	Each Pair: Aluminum Mylar
DRAIN WIRE	Each Pair: 24 AWG 7 Strand Tinned Copper
JACKET	Low-Smoke PVC .018"
JACKET COLOR	Black Jacket
MARKING	SMARTWIRE PRO A/V A B C D E 0 1 2 3 4 5 6 7 8 9 22 AWG C(UL)US CMP ROHS MADE IN THE USA
OVERALL DIAMETER	.175" Nom.
CABLE WEIGHT	21 Lbs/Mft.
CAPACITANCE	50 pF/Ft. Nom.
IMPEDANCE	38 Ohms
TEMPERATURE RATING	0 C to 75 C / 300 Volt

INDUSTRY STANDARDS

FLAME RATING	Approved For Plenum Use Without Conduit Per NFPA 262 Flame Test
AGENCY APPROVALS	NEC Article 800; UL Listed C(UL)US CMP, RoHS Compliant, Made in the USA

All specifications referenced are nominal measurements unless otherwise noted.

© Windy City Wire, Cable Technology & Products, LLC.
All rights reserved.