

PART NUMBER 22-2PREPSP-WHT

UL Listed and Rated Type CMP Multi-Pair Each Pair Shielded Plenum Cable



CABLE SPECIFICATIONS

DESCRIPTION	22 AWG 2 Pair Bare Copper, Individually Shielded Plenum, UL Listed C(UL)US CMP
CONDUCTOR	22 (7/30 Bare Copper)
INSULATION	Low-Smoke PVC .008"
COLOR CODE	Black/Red, White/Green
DRAIN WIRE	Each Pair: 22 AWG 7 Strand Tinned Copper
JACKET COLOR	White Jacket
OVERALL DIAMETER	.175" Nom.
CABLE WEIGHT	21 Lbs/Mft.
CAPACITANCE	50 pF/ft Nom.
TEMPERATURE RATING	0 C to 75 C / 300 Volt

INDUSTRY STANDARDS

FLAME RATING	Approved For Plenum Use Without Conduit Per NFPA 262 Flame Test [®]
AGENCY APPROVALS	NEC Article 800; UL Listed C(UL)US CMP, RoHS Compliant, Made in the USA



All specifications referenced are nominal measurements unless otherwise noted.



WINDY CITY WIRE • T 800.379.1191 • windycitywire.com

© Windy City Wire, Cable Technology & Products, LLC.
All rights reserved.