PART NUMBER 2202PBR-BLK

UL Listed and Rated Type CMP Multi-Conductor Non-Shielded Plenum Cable

■ 0275/0725 FT ● SMA	WIRE(TM) DEVICE/ZONE A B C D E 0 1 2 3 4 5 6 7 8 9	
CABLE SPECIFICATION		
DESCRIPTIO	22 AWG 2 Conductor Bare Copper, Non-Shielded Plenum, UL Listed C(UL)US CMP	
CONDUCTO	22 (7/30 Bare Copper)	
INSULATIO	Low-Smoke PVC .008"	
COLOR COD	Black/Red	
SHIEL	N/A	
DRAIN WIR	N/A	
JACKE	Low-Smoke PVC .018"	
JACKET COLO	Black Jacket	
MARKIN	SMARTWIRE DEVICE / ZONE A B C D E 0 1 2 3 4 5 6 7 8 9 22 AWG C(UL)US CMF MADE IN THE USA	P ROHS
OVERALL DIAMETE	.126" Nom.	
CABLE WEIGH	10 Lbs/Mft.	
CAPACITANC	20 pF/Ft. Nom.	
IMPEDANC	94 Ohms	
TEMPERATURE RATIN	0 C to 75 C / 300 Volt	
INDUSTRY STANDARD		

INDUSTRY STANDARDS

WINDY CITY

 FLAME RATING
 Approved For Plenum Use Without Conduit Per NFPA 262 Flame Test

 AGENCY APPROVALS
 NEC Article 800; UL Listed C(UL)US CMP, RoHS Compliant, Made in the USA



All specifications referenced are nominal measurements unless otherwise noted.

WIRE • T 800.379.1191 • windycitywire.com • [©] WindyCityWire, Cable Technology & Products, LLC. All rights reserved.