PART NUMBER 2202SP-RED

UL Listed and Rated Type CMP Multi-Conductor Shielded Plenum Cable

| ■ 0275/0725 FT ● | SMARTW | 'IRE(TM) | DEVICE/ZONE | A B C D E O 1 | 1 2 3 4 5 6 7 8 9 | | SMARTWIRE GLIDE TECHNOLOGY | |
|------------------|--------|---|----------------|---------------|-------------------|--|----------------------------------|--|
| CABLE SPECIFICAT | IONS | | | | | | | |
| DESCRIPTION | | 22 AWG 2 Conductor Bare Copper, Shielded Plenum, UL Listed C(UL)US CMP | | | | | | |
| CONDU | JCTOR | 22 (7/30 | Bare Copper) | | | | | |
| INSULATION | | Low-Smoke PVC .008" | | | | | | |
| COLOR | CODE | Black/W | nite | 10.0 | | | | |
| LAY LE | NGTH | 2.5" LHL (approx. 4.8 TPF) | | | | | | |
| S | HIELD | Aluminu | n Mylar | | | | | |
| DRAIN | WIRE | 24 AWG 7 Strand Tinned Copper | | | | | | |
| J | ACKET | Low-Sm | oke PVC .018" | | | | | |
| JACKET C | COLOR | Red Jac | ket | 1 H. | | | | |
| MAF | RKING | SMARTWIRE DEVICE / ZONE A B C D E 0 1 2 3 4 5 6 7 8 9 22 AWG C(UL)US CMP ROHS MADE IN THE USA | | | | | (UL)US CMP ROHS | |
| OVERALL DIAN | METER | .126" No | m. | | | | | |
| CABLE W | EIGHT | 12 Lbs/M | lft. | | | | ß | |
| CAPACIT | TANCE | 51 pF/ft | Nom. | | _ | | | |
| IMPEC | DANCE | 37 Ohms | ; | | | | | |
| TEMPERATURE R/ | ATING | 0 C to 7 | 5 C / 300 Volt | | | | | |
| INDUSTRY STAND | ARDS | | | | | | | |

INDUSTRY STANDARDS

| FLAME RATING | Approved For Plenum Use Without Conduit Per NFPA 262 Flame Test |
|------------------|---|
| AGENCY APPROVALS | NEC Article 800; UL Listed C(UL)US CMP, RoHs Compliant, Made in the USA |



All specifications referenced are nominal measurements unless otherwise noted.

WINDY CITY WIRE T 800.379.1191 windycitywire.com
^{© Windy City Wire, Coble Technology & Products, LLC.}
All rights reserved.