## PART NUMBER 2202SP-WHT-GRN

UL Listed and Rated Type CMP Multi-Conductor Shielded Plenum Cable

■ 0275/0725 FT ●	SMARTWIRE(TM)	DEVICE/ZONE	A  B  C  D  E  O  1  2  3  4	56789	<b>K</b>		
ABLE SPECIFICAT DESCRI		G 2 Conductor Bare Co	pper, Shielded Plen	um, UL List	ed C(UL)US CI	MP	
CONDU	<b>CONDUCTOR</b> 22 (7/30		/30 Bare Copper)				
INSUL	ATION Low-Sr	noke PVC .008"					
COLOR	CODE Black/	Black/White					
LAY LE	<b>NGTH</b> 2.5" LH	L (approx. 4.8 TPF)					
s	HIELD Alumin	um Mylar					
DRAIN	WIRE 24 AW	G 7 Strand Tinned Cop	per				
J	ACKET Low-Sr	noke PVC .018"					
JACKET (	COLOR White	White Jacket with Green Stripe					
MAI		WIRE DEVICE / ZONE N THE USA	A B C D E 0 1 2 3	45678	9 22 AWG	C(UL)US CMP ROHS	
OVERALL DIA	METER .126"	lom.					
CABLE W	EIGHT 12 Lbs	12 Lbs/Mft. 51 pF/ft Nom.					
CAPACI	TANCE 51 pF/1						
IMPE	DANCE 37 Ohr	าร					
TEMPERATURE R	ATING 0 C to	75 C / 300 Volt					

## INDUSTRY STANDARDS

FLAME RATING	Approved For Plenum Use Without Conduit Per NFPA 262 Flame Test
AGENCY APPROVALS	NEC Article 800; UL Listed C(UL)US CMP, RoHs Compliant, Made in the USA



All specifications referenced are nominal measurements unless otherwise noted.

