PART NUMBER 2202SP-WHT-YLW

UL Listed and Rated Type CMP Multi-Conductor Shielded Plenum Cable

■ 0275/0725 FT ●	SMARTWIRE(TM)	DEVICE/ZONE A B C D E 0 1 2 3 4 5 6 7 8 9	
ABLE SPECIFICAT DESCRI		2 Conductor Bare Copper, Shielded Plenum, UL Listed C(UL)US CMP	
CONDUCTOR 22 (7/30) Bare Copper)	
INSULATION Low-Sm		oke PVC .008"	
COLOR	CODE Black/W	hite	
	ENGTH 2.5" LH	(approx. 4.8 TPF)	
S	HIELD Aluminu	m Mylar	
DRAIN	WIRE 24 AWG	7 Strand Tinned Copper	
J	ACKET Low-Sm	oke PVC .018"	
JACKET	COLOR White	White Jacket with Yellow Stripe	
MA		VIRE DEVICE / ZONE A B C D E 0 1 2 3 4 5 6 7 8 9 22 AWG C(UL)US CMP ROHS	
OVERALL DIA	METER .126" N	om.	
CABLE W	EIGHT 12 Lbs/	Aft.	
CAPACI	TANCE 51 pF/f	Nom.	
IMPE	DANCE 37 Ohm	s	
TEMPERATURE R	ATING 0 C to	75 C / 300 Volt	

INDUSTRY STANDARDS

FLAME RATING	Approved For Plenum Use Without Conduit Per NFPA 262 Flame Test
AGENCY APPROVALS	NEC Article 800; UL Listed C(UL)US CMP, RoHs Compliant, Made in the USA



All specifications referenced are nominal measurements unless otherwise noted.

