PART NUMBER 2202SP-YLW

UL Listed and Rated Type CMP Multi-Conductor Shielded Plenum Cable

■ 0275/0725 FT ●	SMARTWIRE(T	M) DEVICE/ZONE	ABCDE012	3 4 5 6 7 8 9	C.	TECHNOLOGY.		
CABLE SPECIFICAT DESCRII		AWG 2 Conductor Bare Co	pper, Shielded Ple	enum, UL List	ed C(UL)US CMF	2		
CONDU	CONDUCTOR 22 (7/30		7/30 Bare Copper)					
INSUL	ATION Lo	w-Smoke PVC .008"						
COLOR	CODE Bla	Black/White						
LAY LE	NGTH 2.5	2.5" LHL (approx. 4.8 TPF)						
S	HIELD Alu	ıminum Mylar						
DRAIN	WIRE 24	AWG 7 Strand Tinned Cop	per					
J	ACKET Lo	w-Smoke PVC .018"						
JACKET C	COLOR Ye	llow Jacket						
MAR		ARTWIRE DEVICE / ZONE DE IN THE USA	A B C D E 0 1 2	3 4 5 6 7 8	9 22 AWG C(UL)US CMP ROHS		
OVERALL DIAM	METER .12	26" Nom.						
CABLE W	EIGHT 12	Lbs/Mft.				ß		
CAPACIT	TANCE 51	51 pF/ft Nom.						
IMPE	DANCE 37	Ohms						
TEMPERATURE R	ATING 0	C to 75 C / 300 Volt						

INDUSTRY STANDARDS

FLAME RATING	Approved For Plenum Use Without Conduit Per NFPA 262 Flame Test
AGENCY APPROVALS	NEC Article 800; UL Listed C(UL)US CMP, RoHs Compliant, Made in the USA



All specifications referenced are nominal measurements unless otherwise noted.

WINDY CITY WIRE T 800.379.1191 windycitywire.com
^{© Windy City Wire, Coble Technology & Products, LLC.}
All rights reserved.