PART NUMBER 2202SPBR-BLK

UL Listed and Rated Type CMP Multi-Conductor Shielded Plenum Pro A/V

■ 0275/0725 FT •

SMARTWIRE(TM)

A B C D E 0 1 2 3 4 5 6 7 8 9





CABLE SPECIFICATIONS

DESCRIPTION 22 AWG 2 Conductor Bare Copper, Shielded Plenum, UL Listed C(UL)US CMP

CONDUCTOR 22 (7/30 Bare Copper) INSULATION Low-Smoke PVC .008"

COLOR CODE Black/Red

> SHIELD Aluminum Mylar

DRAIN WIRE 24 AWG 7 Strand Tinned Copper

> JACKET Low-Smoke PVC .018"

JACKET COLOR Black Jacket

> SMARTWIRE PRO A/V A B C D E 0 1 2 3 4 5 6 7 8 9 22 AWG C(UL)US CMP ROHS MADE IN **MARKING**

THE USA

OVERALL DIAMETER .126" Nom.

> CABLE WEIGHT 12 Lbs/Mft.

51 pF/Ft. Nom. CAPACITANCE

IMPEDANCE 37 Ohms

DC RESISTANCE 16.9 Ohms/Mft. maximum @ 20 C

TEMPERATURE RATING 0 C to 75 C / 300 Volt

INDUSTRY STANDARDS

Approved For Plenum Use Without Conduit Per NFPA 262 Flame Test **FLAME RATING**

AGENCY APPROVALS NEC Article 800; UL Listed C(UL)US CMP, RoHS Compliant, Made in the USA







All specifications referenced are nominal measurements unless otherwise noted.