PART NUMBER 2203SP-JCI-BLU

UL Listed and Rated Type CMP Multi-Conductor Shielded Plenum Cable

■ 0275/0725 FT •

TEMPERATURE CONTROL SYSTEM

FC BUS A B C D E 0 1 2 3 4 5 6





CABLE SPECIFICATIONS

DESCRIPTION 22 AWG 3 twisted Conductor Bare Copper, Shielded Plenum, UL Listed C(UL)US CMP

CONDUCTOR 22 (7/30 Bare Copper) **INSULATION** Low-Smoke PVC .008"

COLOR CODE Black/White/Blue

LAY LENGTH 2.5" LHL (approx. 4.8 TPF)

SHIELD Aluminum Mylar

DRAIN WIRE 24 AWG 7 Strand Tinned Copper

JACKET Low-Smoke PVC .018"

JACKET COLOR Blue

MARKING TEMPERATURE CONTROL SYSTEM FC BUS A B C D E 0 1 2 3 4 5 6 7 8 9 22 AWG C(UL)US CMP

ROHS MADE IN THE USA

OVERALL DIAMETER .134" Nom.

CABLE WEIGHT 15 Lbs/Mft.

CAPACITANCE 51 pF/Ft. Nom.

IMPEDANCE 37 Ohms

TEMPERATURE RATING 0 C to 75 C / 300 Volt

INDUSTRY STANDARDS

FLAME RATING Approved For Plenum Use Without Conduit Per NFPA 262 Flame Test

AGENCY APPROVALS NEC Article 800; UL Listed C(UL)US CMP, RoHS Compliant, Made in the USA





