## PART NUMBER 2203SP-JCI-YLW

UL Listed and Rated Type CMP Multi-Conductor Shielded Plenum Cable

■ 0275/0725 FT •

TEMPERATURE CONTROL SYSTEM

FC BUS





## **CABLE SPECIFICATIONS**

DESCRIPTION 22 AWG 3 Conductor Bare Copper, Shielded Plenum, UL Listed C(UL)US CMP

**CONDUCTOR** 22 (7/30 Bare Copper) INSULATION Low-Smoke PVC .008"

**COLOR CODE** Black/White/Yellow

> SHIELD Aluminum Mylar

**DRAIN WIRE** 24 AWG 7 Strand Tinned Copper

> JACKET Low-Smoke PVC .018"

**JACKET COLOR** Yellow

> TEMPERATURE CONTROL SYSTEM FC BUS A B C D E 0 1 2 3 4 5 6 7 8 9 22 AWG C(UL)US CMP **MARKING**

ROHS MADE IN THE USA

**OVERALL DIAMETER** .134" Nom.

> CABLE WEIGHT 15 Lbs/Mft.

51 pF/Ft. Nom. CAPACITANCE

**IMPEDANCE** 37 Ohms

**TEMPERATURE RATING** 0 C to 75 C / 300 Volt

**INDUSTRY STANDARDS** 

Approved For Plenum Use Without Conduit Per NFPA 262 Flame Test **FLAME RATING** 

**AGENCY APPROVALS** NEC Article 800; UL Listed C(UL)US CMP, RoHS Compliant, Made in the USA







All specifications referenced are nominal measurements unless otherwise noted.